


	E-Nova NuVinci (G) (BV)	E-Nova NuVinci (L) (BVL)					
Frame sizes	54-57-60cm	47-50-53-56-59cm					
Frame description	Completely hand-built Super Smooth TIG-welded frame. Tubes manufactured in double- hardened and double-butted 6061 aluminium. Down tube with integrated shifter and brake cables Equipped with: integrated Bosch engine, headset and basements for all accessories and unique KOGA chain tension system						
Front fork	KOGA Feather Lightweight - Ball bearing guided suspension fork - Travel 35 mm	KOGA Feather Lightweight - Ball bearing guided suspension fork - Travel 35 mm					
Headset	Industrial bearing - Integrated in frame	Industrial bearing - Integrated in frame					
Colour	Warm Grey Metallic	Warm Grey Metallic					
Handlebar	KOGA Touring alloy	KOGA Touring alloy					
Stem	KOGA Justera - Adjustable A-head	KOGA Justera - Adjustable A-head					
Grips	KOGA Ergonomic	KOGA Ergonomic					
Shift lever (r)	NuVinci Harmony Advanced Controller - Auto/Manual shift option	NuVinci Harmony Advanced Controller - Auto/Manual shift option					
Disc-/Hydraulic brake set (f)	Magura HS-11 Hydraulic rimbrake - Excellent braking power maintenance free - Turbo Pad Adjustment - Reach Adjust - Easy Bleed Technology	Magura HS-11 Hydraulic rimbrake - Excellent braking power maintenance free - Turbo Pad Adjustment - Reach Adjust - Easy Bleed Technology					
Disc-/Hydraulic brake set (r)	Magura HS-11 Hydraulic rimbrake - Excellent braking power maintenance free - Turbo Pad Adjustment - Reach Adjust - Easy Bleed Technology	Magura HS-11 Hydraulic rimbrake - Excellent braking power maintenance free - Turbo Pad Adjustment - Reach Adjust - Easy Bleed Technology					
Shifter cable	Stainless steel inner cable -Flexible outer cable with teflon tube for light shifting	Stainless steel inner cable -Flexible outer cable with teflon tube for light shifting					
Chain	KMC X1 EPT	KMC X1 EPT					
Front hub	Shimano Deore LX - Double contact sealing for low maintenance and increased service life	Shimano Deore LX - Double contact sealing for low maintenance and increased service life					
Rear hub	NuVinci N380 - Continuously Variable Transmission (CVT) technology is a Continuously Variable Planetary (CVP) - Wide Gear Ratio - Maintainance free - Silent	NuVinci N380 - Continuously Variable Transmission (CVT) technology is a Continuously Variable Planetary (CVP) - Wide Gear Ratio - Maintainance free - Silent					
Tires	Schwalbe Energizer 37 mm - Green Guard protection - Side reflection	Schwalbe Energizer 37 mm - Green Guard protection - Side reflection					
Tube	Schwalbe	Schwalbe					
Rims	Exal EL19-622 Strong alloy - Double wall and Optimised Nipple Contact 36 holes/ KOGA KM19-622 XLite alloy - Double wall and double eyeletted 36 holes - Durable finished	Exal EL19-622 Strong alloy - Double wall and Optimised Nipple Contact 36 holes/ KOGA KM19-622 XLite alloy - Double wall and double eyeletted 36 holes - Durable finished					
Rim tape	Hermanns innertube protective	Hermanns innertube protective					
Spokes	Sapim stainless - Cold forged reinforced	Sapim stainless - Cold forged reinforced					
Saddle	KOGA Komforza	KOGA Komforza					
Seat post	KOGA alloy - Shock absorbing - Safety Clamp construction - Travel 30mm	KOGA alloy - Shock absorbing - Safety Clamp construction - Travel 30mm					
Seat clamp	KOGA - Alloy	KOGA - Alloy					
Crank set	Miranda 18T	Miranda 18T					
Bottom bracket	Bosch BracketEngine 250W, 48Nm, 36V (System: Active Cruise Line)	Bosch BracketEngine 250W, 48Nm, 36V (System: Active Cruise Line)					
Pedals	KOGA Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body	KOGA Sole-Mate - Concaved anti slip layer - Industrial bearing - ED coated body					
Cassette	NuVinci 16T	NuVinci 16T					
Pump	KOGA Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip	KOGA Telescopic with alloy barrel - Schrader and Presta Fit - High Pressure/ Big Volume switch - Ergonomic hinge grip					
Bottle	Tacx Source Solid - Easy refill						
Bottle holder	Tacx Allure						
Bell	Widek Compact	Widek Compact					
Chain guard	KOGA DeFenz	KOGA DeFenz					
Mudguard (f)	SKS B-45	SKS B-45					
Mudguard (r)	SKS B-45	SKS B-45					
Headlight	B&M Lumotec EYC T - IQ2 Long life LED technology 50 Lux - Daylight function - KBA approved	B&M Lumotec EYC T - IQ2 Long life LED technology 50 Lux - Daylight function - KBA approved					
Rear light	Spanninga Plateo	Spanninga Plateo					
Rear carrier	KOGA frame integrated - Battery Integrated - Alloy hollow tubing max 20 kg - Durable black finish	KOGA frame integrated - Battery Integrated - Alloy hollow tubing max 20 kg - Durable black finish					
Rubber strap	KOGA TriFlex	KOGA TriFlex					
Kickstand	Pletscher Comp - Superb stability - Powdercoated durable finish	Pletscher Comp - Superb stability - Powdercoated durable finish					
Ring lock	Trelock RS 450 - ART ** Approved	Trelock RS 450 - ART ** Approved					
Display	Bosch Intuvia	Bosch Intuvia					
Battery	Bosch Li-lon 500Wh (36V*11Ah) Removable from rear carrier	Bosch Li-lon 500Wh (36V* 1 1 Ah) Removable from rear carrier					
Accessories	HandlebarControl Unit	HandlebarControl Unit					
Gears	Continuously Variable Transmission (CVT)	Continuously Variable Transmission (CVT)					



© 2015 KOGA reserves the right to make changes to specifications and/or prices without further notice. Although this brochure has been compiled with the utmost care, no liability can be taken for any remaining errors of any type. Reproduction of this publication is prohibited unless expressly permitted in writing by KOGA.

Gents

Size	T/T	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	Н/Т	Reach	Stack
54	572	467	1089	55	42	69,5	72,0	85	130	386	580
57	584	467	1076	55	42	70,5	71,0	78	150	376	604
60	596	467	1091	55	42	70,5	71,0	78	175	380	627

Ladies

Size	1/1	C/S	Wheelbase	BB-Drop	Rake	H/T Angle	S/T Angle	Trail	H/T	Reach	Stack
47	562	467	1074	55	42	69,5	72,0	85	170	357	632
50	569	467	1081	55	42	69,5	72,0	85	180	361	642
53	576	467	1089	55	42	69,5	72,0	85	190	365	651
56	583	467	1072	55	42	70,5	71,0	<i>7</i> 8	200	354	665
59	590	467	1079	55	42	<i>7</i> 0,5	71,0	<i>7</i> 8	210	358	674